





Combination Systems

For Box Sealing and Strapping Application



carton sealing machine


Semi-Auto Strapping machine

Fully-Auto Strapping machine

Stretch Wrapping machine


We pack your way

Customize
Packaging
Solutions



This basic **2 in 1** combo machine is good for **uniform** size cartons. It provides continuous sealing and strapping. The packaging options can be chosen from single strap or double strap, also with adjustable strapping position for different carton length. Each machine can be used individually when needed. The carton sealer has 60 sec. auto-stop device to save power consumptions. The **CAT** strapping machine features **Auto strap feeding** from top improves productivity and **Auto strap ejector** reduces downtime.


* Operation Flow Diagram




Manually
fold all
flaps




Feed into
sealing
machine



Sealing & Strapping



Sealing (**bypass strapping**)



Strapping (**bypass sealing, with flap plate extension to hold down top flaps entering strapping machine**).





* System Video

A: PW-553SB	Uniform Carton Sealer with Side Belt Drive
Tape Width	2" or 3" OPP or Paper tape
Sealing Range	2" L300~700 x W120~500 x H110~500 3" L300~700 x W145~500 x H110~500 (mm)
Loading weight	30 kg (50 kg options)
Belt speed	15M/Min.
Table height	550 ~ 810 mm (adjustable legs)
Power Supply	3PH 220V, 380V, 415V, 440V, 50/60Hz




B: PW-0860CAT	Automatic Strapping Machine with Auto Strap Feed
Strap Width	9mm, 12mm, 15mm, 19mm
Tension Range	Up to 70 kg
Strapping speed	28 straps per minute
Package Size	Max. W500 x H500 Min. W120 x H110 (with PW-553SB)
Package Size	Max. W800 x H550 Min. W100 x H30 (use alone)
Table height	810 mm as standard or 730 mm (options)
Power Supply	3PH 220V, 380V, 415V, 440V, 50/60Hz




* Options

- Extension roller table at in feed
- Stainless steel frame
- Close-type roller table to increase loading capacity
- Retractable tapping head (bypass sealing)
- Machine extension upon request

Oh. So. Compact.



Oh. So. Costly.



Machine Type	Description
PW-553SB	Sealing Machine (extended side belt)
PW-0860CAT	Automatic Strapping Machine (Free Roller Tabletop)

Pros

- Quick set up
- Cost effective layout
- Wider range box sizes
- Less maintenance costs
- Less power consumption

Cons

- Without buffer conveyor
- One package in and out at a time (depending on box length)


Machine Type	Description
PW-553S	Sealing Machine (without extended side belt)
PW-0860CATS2B	Fully Automatic Strapping Machine (Belt Driven Tabletop)

Pros

- Better transit buffer with extra conveyor in between
- Lesser idle time


Cons

- Require more space
- Box size range is constrained
- More maintenance costs
- More wearable components (belts)
- More power consumption




This **2 in 1** basic combo machine is designed for **uniform** size cartons. It provides continuous sealing and strapping and features **left/right flap folding mechanism**. The packaging options can be chosen from single strap or double strap, also with adjustable strapping position for different carton length. Each machine can be used individually when needed. The carton sealer has 60 sec. auto-stop device to save power consumptions. The **CAT** strapping machine features **Auto strap feeding** from top improves productivity and **Auto strap ejector** reduces downtime.

* Operation Flow Diagram




Manually fold
down rear flap


Feed into
sealing
machine



Sealing & Strapping




Sealing (**bypass strapping**)



Strapping (**bypass sealing, with flap plate extension to hold down top flaps entering strapping machine**).


Left/Right Flap fold mechanism




A: PW-553SBLF	Uniform Carton Sealer with Side Belt Drive + Top Flap Folding
Tape Width	2" or 3" OPP or Paper tape
Sealing Range	2"/ 3" L300~500 x W200/225~500 x H110~500 mm
Loading weight	30 kg (50 kg options)
Belt speed	15M/Min.
Table height	550~810 mm (adjustable legs)
Power Supply	3PH 220V, 380V, 415V, 440V, 50/60Hz



B: PW-0860CAT	Automatic Strapping Machine with Auto Strap Feed
Strap Width	9mm, 12mm, 15mm, 19mm
Tension Range	Up to 70 kg
Strapping speed	28 straps per minute
Package Size	Max. W500 x H500 Min. W200 x H110 (with PW-553SBLF)
Package Size	Max. W800 x H550 Min. W100 x H30 (use alone)
Table height	810 mm as standard and 730 mm (options)
Power Supply	3PH 220V, 380V, 415V, 440V, 50/60Hz




Unit: mm




* Options

- Extension roller table at in feed
- Stainless steel frame
- Close-type roller table to increase loading capacity
- Retractable tapping head (bypass sealing)
- Machine extension upon request

Oh. So. Easy.



Oh. So. Costly.



Machine Type	Description
PW-553SBLF	Sealing Machine (extended side belt)
PW-0860CAT	Automatic Strapping Machine (Free Roller Tabletop)

Pros

- Quick set up
- Cost effective layout
- Wider range box sizes
- Less maintenance costs
- Less power consumption

Cons

- Without buffer conveyor
- One package in and out at a time (depending on box length)


Machine Type	Description
PW-553SF	Sealing Machine (without extended side belt)
PW-0860CATS2B	Fully Automatic Strapping Machine (Belt Driven Tabletop)

Pros

- Better transit buffer with extra conveyor in between
- Lesser idle time



Cons

- Require more space
- Box size range is constrained
- More maintenance costs
- More wearable components (belts)
- More power consumption




This **2 in 1** combo machine is designed for **uniform** size cartons. It provides continuous sealing and strapping and features **all top flap folding mechanism**. The packaging options can be chosen from single strap or double strap, also with adjustable strapping position for different carton length. Each machine can be used individually when needed. The carton sealer has 60 sec. auto-stop device to save power consumptions. The **CAT** strapping machine features **Auto strap feeding** from top improves productivity and **Auto strap ejector** reduces downtime.

* Operation Flow Diagram




Automatic Flap fold mechanism




A: PW-557FB	Uniform Carton Sealer with Side Belt Drive + Top Flap Folding
Tape Width	2" or 3" OPP or Paper tape
Sealing Range	2"/3" L200~600 x W120/145~500 x H110~500 mm
Loading weight	30 kg (50 kg options)
Belt speed	15M/Min.
Table height	550~810 mm (adjustable legs)
Power Supply	3PH 220V, 380V, 415V, 440V, 50/60Hz




B: PW-0860CAT	Automatic Strapping Machine with Auto Strap Feed
Strap Width	9mm, 12mm, 15mm, 19mm
Tension Range	Up to 70 kg
Strapping speed	28 straps per minute
Package Size	Max. W500 x H500 Min. W120 x H110 (with PW-557FB)
Package Size	Max. W800 x H550 Min. W100 x H30 (use alone)
Table height	810 mm as standard and 730 mm (options)
Power Supply	3PH 220V, 380V, 415V, 440V, 50/60Hz



Auto strap feeding



Push up lever




* Options

- Extension roller table at in feed
- Stainless steel frame
- Close-type roller table to increase loading capacity
- Retractable tapping head (bypass sealing)
- Machine extension upon request
- Detection for low tape and sealing

Unit: mm

Oh. So. Efficient.



Machine Type	Description
PW-557FB	Sealing Machine (extended side belt)
PW-0860CAT	Automatic Strapping Machine (Free Roller Tabletop)


Pros

- Quick set up
- Cost effective layout
- Wider range box sizes
- Less maintenance costs
- Less power consumption

Cons

- Without buffer conveyor
- One package in and out at a time (depending on box length)

Oh. So. Costly.



Power Roller Table

Power Roller Table


Machine Type	Description
PW-557F	Sealing Machine (without extended side belt)
PW-0860CATS2B	Fully Automatic Strapping Machine (Belt Driven Tabletop)

Pros

- Better transit buffer with extra conveyor in between
- Lesser idle time

Cons


- Require more space
- Box size range is constrained
- More maintenance costs
- More wearable components (belts)
- More power consumption



Standard Safety doors

This **2 in 1** combo machine is designed for **random** size cartons. It provides continuous sealing and strapping without the need to adjust the carton sealer manually when changing carton sizes. It can switch to **height memory** function for batch production. The packaging options can be chosen from single strap or double strap, also with adjustable strapping position for different carton length. Each machine can be used individually when needed. The carton sealer has 60 sec. auto-stop device to save power consumptions. The **CAT** strapping machine features **Auto strap feeding** from top improves productivity and **Auto strap ejector** reduces downtime.


* Operation Flow Diagram




Manually
fold all
flaps




Feed into
sealing
machine



Sealing & Strapping



Sealing (**bypass strapping**)



Strapping (**bypass sealing, with flap plate extension to hold down top flaps entering strapping machine**)


* System Video




A: PW-555AB	Random Carton Sealer with Side Belt Drive
Tape Width	2" or 3" OPP or Paper tape
Sealing Range	2"/3" L300~700 x W120/145~500 x H150~500 mm
Loading weight	30 kg (50 kg options)
Belt speed	15M/Min.
Table height	550~810 mm (adjustable legs)
Power Supply	3PH 220V, 380V, 415V, 440V, 50/60Hz



B: PW-0860CAT	Automatic Strapping Machine with Auto Strap Feed
Strap Width	9mm, 12mm, 15mm, 19mm
Tension Range	Up to 70 kg
Strapping speed	28 straps per minute
Package Size	Max. W500 x H500 Min. W120 x H150 (with PW-555AB)
Package Size	Max. W800 x H550 Min. W100 x H30 (use alone)
Table height	810 mm as standard and 730 mm (options)
Power Supply	3PH 220V, 380V, 415V, 440V, 50/60Hz



Unit: mm



* Options

- Extension roller table at in feed
- Stainless steel frame
- Close-type roller table to increase loading capacity
- Retractable tapping head (bypass sealing)
- Machine extension upon request
- **Detection for low tape and sealing failure (PLC control)**

Oh. So. Convenient.



Machine Type	Description
PW-555AB	Sealing Machine (extended side belt)
PW-0860CAT	Automatic Strapping Machine (Free Roller Tabletop)


Pros

- Quick set up
- Cost effective layout
- Wider range box sizes
- Less maintenance costs
- Less power consumption

Cons

- Without buffer conveyor...
- One package in and out at a time (depending on box length)

Oh. So. Costly.



Machine Type	Description
PW-555A	Sealing Machine (without extended side belt)
PW-0860CATS2B	Fully Automatic Strapping Machine (Belt Driven Tabletop)


Pros

- Better transit buffer with extra conveyor in between
- Lesser idle time

Cons


- Require more space
- Box size range is constrained
- More maintenance costs
- More wearable components (belts)
- More power consumption

* System Video




This **fully automatic high speed** carton sealing and strapping system is designed for **random** size cartons. The carton width and height is **pre-detected** at in feed and with **Servo motor drives** for instant and precise positioning. The capacity is **16 cartons per minute** and folds all four sides of top flaps, it is also suited for system operation with **in-feed flow control** and alarm/sensors for low tape and sealing failure as standards. A power roller conveyor at out feed for delivering the cartons to the strapping position.

* Operation Flow Diagram





High Speed Tape Head



















A: PW-569SAF	High Speed Random Carton Sealer
Tape Width	2" or 3" OPP or Paper tape
Sealing Range	2"/3" L300~500 x W200/225~400 x H160~500 mm
Loading weight	30 kg (50 kg options)
Belt speed	33M/Min. (14~16 Cartos per min.)
Table height	550~810 mm (adjustable legs)
Power Supply	3PH 220V, 380V, 415V, 440V, 50/60Hz
Air Supply	6kgf/cm ²



B: PW-0860CATS2B	Automatic Strapping Machine with Auto Strap Feed—Belt driven table
Strap Width	9mm, 12mm, 15mm, 19mm
Tension Range	Up to 70 kg
Strapping speed	28 straps per minute
Package Size	Max. W400 x H500 Min. W200 x H160 (with PW-569SAF)
Package Size	Max. W800 x H550 Min. W100 x H30 (use alone)
Table height	810 mm as standard and 730 mm (options)
Power Supply	3PH 220V, 380V, 415V, 440V, 50/60Hz



Unit: mm


Tape Head	C1	C1 Retractable	C1 Overlap	C3	C3 Segment	C3 Narrow	Speedy	C6 Ergo
Specification								
Tape Sizes	2" or 3"	2" or 3"	2" or 3"	1.5" or 2"	1.5"	2"	2" or 3"	2" or 3"
Tape Overlap (mm)	40 ± 5 60 ± 5 70 ± 5 90 ± 5	40 ± 5 60 ± 5 70 ± 5 90 ± 5	40 ± 5 60 ± 5 70 ± 5 90 ± 5	30 ± 5	n/a	30 ± 5	60 ± 5	60 ± 5
Compatible Models	551TB, 552TB, 553S, 554TS, 555AU, 556AU, 557F, 558F, 559AF and custom made	551TB, 552TB, 553S, 554TS, 555AU, 556AU, 557F, 558F, 559AF and custom made	551TB, 552TB, 553S, 554TS, 555AU, 556AU, 557F, 558F, 559AF and custom made	562M	562M	562M	569SAF 568AHERT	542S
Functionality	Standard General	Optional function for sealing bypass situation	Extra taping roller to press down the tape	Standard for small boxes	Segmented taping without applying tape overlap	Tall and Narrow boxes	Standard Fully Automatic High Speed Taping	Ergonomic Tape Threading
Package & Sealing Style					Shallow box less than 30mm in Height 	Narrow box 		

All specifications are subject to change without notice.

Extention Roller Table




Extra platform space for better handling.




*Not Compatible with 569SAF sealing machine


Extension Plate for Flaps



Main purpose for sealing bypass mode.
The extension plate helps to press down
top flaps and stabilizing the package
before entering into strapping machine.




Using sealing bypass mode and the
extension flap plate together to further
diversify your packaging requirement.



*Not Compatible with 569SAF sealing machine

Safety Door



Made with acrylic material for window and aluminum frame. It provides
clearer visibility of machine status.

Best suited for Fully Automatic or automatic flap folding sealing machines.

*Not required for Uniform type sealing machine

56, 35th Rd. Taichung Ind. Park,
Taichung 407, TAIWAN

E-mail : packway07@packway.com

TEL : +886 4 2359 1858

FAX : +886 4 2359 7489